





LINCOLN @ Mercury

Motorcraft

Notunda

Material Safety Data Sheet

Product Name:

SAE (5W-20 and 5W-30) Full Synthetic Motor Oil

FIR No.

173414

Level: 1

Version Number:

US-US-1

Release Date: 2005-02-18

1. Product and Company Identification

Product Name:

SAE (5W-20 and 5W-30) Full Synthetic Motor Oil

Product Code:

See Attachment

Application:

Motor Oil

Supplier:

Ford Motor Company

Attention: MSDS Information, P.O. Box 1899

Dearborn, Michigan 48121

1-800-392-3673

Emergency Telephone:

Poison Control Center: 1-800-959-3673

CHEMTREC: U.S. and Canada: 1-800-424-9300 CHEMTREC: International: 1-703-527-3887

2. Composition/Information on Ingredients

This chemical product is a preparation.

Chemical Name	CAS Number	Percent Hazard Concentration Classification
PETROLEUM DISTILLATES HYDROTREATED HEAVY PARAFFINIC	64742-54-7	>60 HAZCOM RSMSPROH
PETROLEUM DISTILLATES, HYDROTREATED MIDDLE	64742-46-7	>10-30 HAZCOM RSMSREST
DIPHENYLAMINE	122-39-4	.1-<1 RSMSREST
		WHMIS 0.1

3. Hazards Identification

Health:

Exposure to oil mist/fume/vapor may cause respiratory tract irritation. Inhalation of mist and vapors may irritate the nose, throat, and lungs. Ingestion may cause slight stomach irritation and discomfort. This product is not expected to cause eye irritation under normal conditions of use. Symptoms of slight eye irritation may result when direct contact occurs.

No skin irritation can be expected from single short-term exposure to this product. Prolonged or repeated contact may produce some

irritation.

Environment:

Material contains a chemical which is a Hazardous Air Pollutant (HAP),

regulated by the United States Clean Air Act.

4. First-Aid Measures

Inhalation:

If inhalation of gas/fume/vapor/dust/mist from the material is excessive (air concentration is greater than the TLV or health effects are noticed).

immediatly remove the affected person(s) to fresh air.

If irritation persists, get medical attention.

Owner: Ford Motor Company

Application: MATS

PRINTED DOCUMENT IS TRANSIENT 1 / 7

Ford Proprietary Official Record

Page:





LINCOLN @ Mercury



Motorcraft

Notunda

Material Safety Data Sheet

Product Name:

SAE (5W-20 and 5W-30) Full Synthetic Motor Oil

FIR No.

173414

Release Date:

Level: 1

2005-02-18

Version Number:

US-US-1

Wash skin with soap and water.

If irritation persists, get medical attention.

Eye Contact:

Skin Contact:

In case of contact with eyes, rinse immediately with plenty of water for

at least 15 minutes and seek medical attention.

If irritation persists, get medical attention.

Ingestion:

If the material is swallowed, get immediate medical attention or advice

-- Do not induce vomiting.

Notes to a Physician:

If the affected person is not breathing, apply artificial respiration.

5. Fire-Fighting Measures

Extinguishing Media:

Alcohol foam (preferred), dry chemical, water.

Specific Methods:

Use water to cool fire-exposed containers, structures, and to protect

personnel.

Specific Hazards:

Flammable at all temperatures above the flash point on contact with an

ignition source.

Irritating and/or toxic fumes and gases may be emitted upon the

product's decomposition.

Empty containers may retain product residue including Flammable or Explosive vapors. Do not cut, drill, grind, or weld near full, partially full,

or empty product containers.

Protection of Firefighters:

Fire fighters should be equipped with NIOSH-approved, self-contained

breathing apparatus (SCBA) and full protective clothing.

6. Accidental Release Measures

Personal Precautions:

Eliminate all sources of ignition or flammables that may come into

contact with a spill of this material.

Wear appropriate protective equipment and clothing during clean-up.

Environmental Precautions:

Do not allow the spilled product to enter public drainage system or

open water courses.

WATER SPILL: Remove from surface by skimming or with suitable absorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in confined waters.

Methods for Cleaning Up:

Contain the discharged material.

Absorb the spilled material with an inert absorbent (nonflammable)

material.

Owner: Ford Motor Company

Application: MATS

Page:

2 /

Ford Proprietary Official Record

PRINTED DOCUMENT IS TRANSIENT







LINCOLN



Motorcraft

Notunda

Material Safety Data Sheet

Product Name:

Version Number:

SAE (5W-20 and 5W-30) Full Synthetic Motor Oil

FIR No.

173414

US-US-1

Level:

Release Date: 2005-02-18

7. Handling and Storage

Handling:

Technical Measures:

Avoid the generation of oil mists.

Precautions and Advice for

Safe Handling:

Elevated temperature or mechanical action may form vapors, mist, or fumes which may be irritating to the eyes, nose, throat, and lungs.

Avoid breathing vapors or mist.

Keep the container closed when not in use.

Storage:

Technical Measures:

No special precautions.

Storage Conditions:

Keep the container tightly closed and in a cool, well-ventilated place.

Store this product away from strong oxidizing agents.

8. Exposure Controls/Personal Protection

Engineering Measures:

Use adequate mechanical ventilation (general and/or local exhaust)

ventilation to maintain exposure below PEL(s) and/or TLV(s).

Control Parameters:

If oil mist is generated, observe the OSHA exposure limit of 5 mg/m3.

Ford Motor Company recommends an exposure limit of 1.0 mg/m3.

Exposure Limits:

Chemical Name

TWA 8 hr

References

DIPHENYLAMINE

10(mg/m3)

ACGIH

OSHA

Personal Protective Equipment:

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must

be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard 29 CFR 1910.134 and/or Canadian Standard CSA Z94.4.

Hand Protection:

Use of impervious gloves is recommended, such as neoprene.

Eye Protection:

Wear safety glasses with side shields.

Skin and Body Protection:

Use of an impervious apron is recommended.

Owner: Ford Motor Company

Application: MATS

Page:

PRINTED DOCUMENT IS TRANSIENT 3 / 7







LINCOLN @ Mercury

Motorcraft

Notunda

Material Safety Data Sheet

Product Name:

SAE (5W-20 and 5W-30) Full Synthetic Motor Oil

FIR No.

173414

Level: Release Date: 2005-02-18

Version Number:

US-US-1

Remove contaminated clothing and wash the skin thoroughly with soap and

water after work.

Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Specific Gravity:

Hygiene Measures:

0.85-0.86

Physical State:

LIQUID

Odor:

PETROLEUM

Color:

AMBER

:Hq

N.AV

Temperature Range During which Changes in Physical State Occur:

Flash Point:

185 °C PMCC

Explosion Properties:

UEL:

N.AV

LEL:

N.AV

Vapor Pressure:

<1@20°C mmHg

Vapor Density:

>1 (AIR=1)

Solubility:

NEGLIGIBLE IN WATER

Viscosity:

43-63@40°C cSt ASTM D445

Evaporation Rate:

<1 (BuAc = 1)

10. Stability and Reactivity

Stability:

This is a stable material.

Hazardous polymerization will not occur.

Conditions and Materials to Avoid:

This product can react with oxidizing materials.

Hazardous Decomposition Products:

Carbon monoxide, carbon dioxide, and other low molecular weight

hydrocarbons.

11. Toxicological Information

Chronic (Long Term) Toxicity:

Base oil severely refined: Not carcinogenic in animal studies.

Representative material passes IP-346, Modified Ames test, and/or

other screening tests.

Continuous long term contact with used motor oil has caused skin

cancer in animal tests.

Owner: Ford Motor Company

Application: MATS

Page:

PRINTED DOCUMENT IS TRANSIENT

Ford Proprietary Official Record

4 / 7

Ford Motor Company

LINCOLN @ Mercury

Motocraft

Notunda

Material Safety Data Sheet

Product Name:

SAE (5W-20 and 5W-30) Full Synthetic Motor Oil

FIR No.

173414

Level: 1

Version Number:

US-US-1

Release Date: 2005-02-18

12. Ecological Information

No specific aquatic data available for this product.

13. Disposal Considerations

Waste from Residues:

Dispose of waste material according to Local, State, Federal, and

Provincial Environmental Regulation.

Waste Disposal - Material should be disposed of separately or with plant used motor oils, indicating the materials potential to cause skin

cancer with prolonged and repeated contact.

Empty containers may contain hazardous residues (vapors, liquid, and/or solid). Do not reuse the empty container without commercial

cleaning or reconditioning.

Contaminated Packaging:

No available information.

Owner: Ford Motor Company

Application: MATS

Page:

5 / 7

PRINTED DOCUMENT IS TRANSIENT









Motorcraft

Notunda

Material Safety Data Sheet

Product Name:

Version Number:

SAE (5W-20 and 5W-30) Full Synthetic Motor Oil

FIR No.

173414

US-US-1

Level: 1

Release Date: 2005-02-18

Official Record

14. Transport Information

U.S. Department of Transportation (DOT) 49 - CFR 172.101

This product is not regulated as a dangerous good.

Canadian Transportation of Dangerous Goods (T.D.G.) -TDGR Schedule II

This product is not regulated as a dangerous good.

Secretary of Communication and Transportation (SCT)- NOM-002-SCT2/1994 (Mexico)

This product is not regulated as a dangerous good.

International and Domestic Air Transportation - ICAO & IATA Section 4.2

This product is not regulated as a dangerous good.

International Water Transportation - IMDG Code Amendment 31-02

This product is not regulated as a dangerous good.

15. Regulatory Information

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372

Material contains a chemical which is a Ford Motor Company Material of Concern. Use and release of this material should be minimized to the greatest extent possible.

16. Other Information

Key/Legend: N.AP = Not applicable; N.AV = not available; ND = Not determined or No data; TLV = Threshold limit value; TWA = Time-weighted average; STEL = Short-term exposure limit; C = Ceiling limit

Preparation Information:

The chemical identification and properties for this material were provided by the manufacturer. For Canadian locations, a manufacturer's MSDS is available upon request. Health and safety information has been evaluated by the Occupational and Environmental Health Sciences Department, Ford Motor Company, National Parts General Office, MD74, 29500 Plymouth Road, Livonia, MI 48150, USA.

Disclaimer:

The information on this data sheet represents our current data and is accurate to the best of our knowledge as to the proper handling of this product under normal conditions and in accordance with the application specified on the packaging and/or technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

PRINTED DOCUMENT IS TRANSIENT Owner: Ford Motor Company Ford Proprietary Application: MATS Page: 6 /









Motorcraft

Notunda

Material Safety Data Sheet

Product Name:

SAE (5W-20 and 5W-30) Full Synthetic Motor Oil

FIR No.

173414

Level: 1

Version Number:

US-US-1

Release Date: 2005-02-18

tac	hment		

Attachment					
Product Code	Container Size	Part of Kit	Kit Product Code		
XO-5W20-DFS	55 U.S. Gallon Drum				
XO-5W20-QFS	1 qt				
XO-5W30-DFS	55 U.S. Gallon Drum				
XO-5W30-QFS	1 qt				

Owner: Ford Motor Company

Application: MATS

PRINTED DOCUMENT IS TRANSIENT

7 / 7 Page:

Ford Proprietary Official Record